



# Separon™ Deoiling Hydrocyclone

## Primary Produced Water Deoiling

Separon™ Deoiling Hydrocyclones ensure effective separation with a cost-effective and space-efficient solution. The advanced generation hydrocyclone geometry optimizes the critical balance between oil removal efficiency and capacity, resulting in finer hydrocarbon separation. Fewer cyclone liners are required compared to traditional systems to treat higher rates of entrained oil while meeting stringent discharge requirements. Options are available for standard units, high turndown design, compartmentalized vessels, pumped systems, and retrofits to existing vessels.

## How It Works

As produced water enters the hydrocyclone, the tangential velocity creates a centrifugal action. The velocity increases causing the heavier fluid (water) to move to the outer wall of the liner while the lighter fluid (oil) moves to the inner core. Water exits at the clean water outlet while due to back pressure, the lighter oil moves axially through the cyclone and exits out the discharge orifice at the opposite end.

## Key Benefits

### Cost Saving


- No moving parts saves maintenance time and costs
- Involute can be inspected without liner disassembly

### Better Performance

- Multiple inlets provide a stable core and increased recovery
- Low and steady pressure loss provides predictable flow rates

### Flexibility

- Superior hydraulic stability even at very low flow rates due to tighter, axisymmetric oil core
- High turndown ratios
- Designed to handle upset situations and slugging of oil and gas
- Choice of profiles to accommodate space and piping limitations
- Available as standalone equipment or complete skid packages



## Standard Features

- ANSI flanged inlet and outlet connections
- Designed to ASME, ANSI, CRN, PED, and NACE industry standards

## Materials of Construction

- Liner Material: Duplex 2205  
Stainless Steel

## Common Applications

- FWKO
- SAGD
- Secondary Recovery
- Disposal Wells
- Subsea Production
- Offshore Production
- Secondary Produced Water Treatment

This brochure is intended for general information purposes only and is not intended as a representation or warranty of any kind, or as a statement of any terms or conditions of sale. The information herein is believed to be correct, but is not warranted for correctness or completeness, or for applicability to any particular customer or situation. © 2024 Enerflex Corporation. All Rights Reserved.